## OPTIONAL ACCESSORIES

### 

- · Positive flow shut off valve
- Allows generator to run unattended

### Two-Wheel Dolly Kit -

- Fits 6kW and 9kW
- · Fold down handle
- 4-wheel dolly kit standard on HPS12

### WINCO Emergency Transfer Switch ———

- Outdoor enclosure
- Premium circuit breaker load center

### Generator Cover -

- Made of heavy canvas
- · Weather resistant
- Large cover for 12kW
- Small cover for 6kW and 9kW

### > Maintenance Kit -

- 10W-30 oil
- Sta-bil fuel stabilizer
- Bosch Platinum spark plug
  - Air filter

### D———— Battery ———

- Interstate 300 CCA
- 6-month free replacement

### o Battery Charger — C

• Smart 3 stage 1.5 amp trickle charger



225 S. Cordova Ave Le Center, MN 56057





IRI-FUEL GENERATOR + GARREN

# HOME POWER







### **SPECIFICATIONS**

MODEL	HPS6000HE*	HPS9000VE	HPS12000HE
ELECTRICAL SPECIFICATIONS			
Starting Watts <sup>(1)</sup>	6,000	9,000	12,000
Run Watts Gasoline	5,500	8,000	10,800
Run Watts LP	N/A	7,200	9,720
Run Watts NG	4,400	6,400	8,640
Voltage	120/240	120/240	120/240
Cont. Amps <sup>(1)</sup>	45.8/22.9	66.7/33.3	90/45
Motor Starting <sup>(1)(2)</sup>	2 hp	4 hp	5 hp
<b>ENGINE DATA</b>			
Make/Model	Honda GX340	B&S Vanguard	Honda GX630
Displacement	389сс	480cc	688cc
Starting System <sup>(3)</sup>	Electric/Recoil	Electric/Recoil	Electric
Fuel Tank Capacity	7 gal	7 gal	15 gal
Low Oil Protection	Standard	Standard	Standard
dba Rating @ 7 Meters	72	77	78
FUEL CONSUMPTION			
Gasoline	1.0 gal/hr	1.3 gal/hr	1.67 gal/hr
LP Vapor	N/A	1.9 gal/hr	2.2 gal/hr
Natural Gas	160 ft <sup>3</sup> /hr	180 ft <sup>3</sup> /hr	200 ft <sup>3</sup> /hr
RECEPTACLES			
120V NEMA 5-20R	2-20 amp	4-20 amp	4-20 amp (GFCI)
120/240 L14-30R	L14-30R -	L14-30R -	L14-30R NEMA 14-60R
GENERAL INFO	RMATION		
Dimensions(LxWxH)	32.75x 22.5x 22	32.75x 22.5x 22	44.7x 36x 33 <sup>(4)</sup>
Shipping Weight	224 lbs	267 lbs	460 lbs
Warranty <sup>(5)</sup>	2 yr	2 yr	2 yr
NOTE: (1) Based on gasoline fuel, derate 10% for LP and 20% for NG (2) Code			

NOTE: (1) Based on gasoline fuel, derate 10% for LP and 20% for NG (2) Code G capacitor start motor (3) Battery NOT included, see individual spec sheets for battery requirements (4) HPS12000HE dimensions include installed wheel kit (5) Prime Power Warranty-120 days. Engine warranty administered by engine manufacturer. Contact your local Honda or B&S service center for warranty assistance. WINCO Inc. can assist in locating appropriate engine warranty support.

### ——— MULTIPLE FUEL ——

Easily change between gasoline, Natural Gas, and Propane\*. You are no longer limited to one resource.

### ○ EPA APPROVED -

EPA approved for use of gasoline, Natural Gas, and Propane\*.

### PORTABLE ---

The convenience of a portable generator with the versatility of multiple fuel sources. No portable unit is better prepared for when life happens.

### ○ COMMERCIAL ENGINES ─ ○

Honda GX and Briggs & Stratton Vanguard engines are known for their denpendability and reliability, Our multi-fuel generators have gone through an extensive application review to maintain a full engine warranty.

### ----- RELIABLE ----

Exceptional engineering ensures these units will work whenever needed.

### ○ RUGGED DESIGN —

Engineered and built tough with steel and powder coat paint.

#### ——— STRONG HISTORY ———

WINCO has been building dependable multi-fuel generators since 1987, making these units the longest lasting on the market.

<sup>\*</sup>HPS6000HE is not EPA certified for LP gas use.